



# Rover GT

by E-TON



Shown with optional equipment

Let the  
**ROVER GT**  
take you there!

Mountain Silver  
Forest Green

Introducing the 2007 E-TON Rover GT Utility Kart. E-TON's brand-new, versatile, unique sport/utility vehicle includes a powerful four-stroke air cooled engine, automatic C.V.T. belt transmission with forward/reverse shifting, a full body frame with a seat belt, and a U.S. Forest Service approved spark arrestor.

The Rover GT meets or exceeds EPA clean air requirements and is eligible for the California Green Sticker. Includes full six month limited factory warranty. This multi-purpose vehicle was designed for appropriate sized riders of all ages

## Optional Accessories

- Portable Cooler
- Helmets and apparel
- Front Cargo Rack
- Rear Cargo basket
- 2 styles of Cargo bags
- Headlight system

All available through your local dealership and our website.

ETON AMERICA.

[www.etonamerica.com](http://www.etonamerica.com)

<b>Engine</b>			
Type	Four cycle air cooled (EPA Compliant) SOHC		
Displacement	88.4cc		
Bore / Stroke	φ47.0 * 51.0mm		
Compression Ratio / Pressure	10.2 : 1 / 120-140psi		
Torque / Power	6.1N ms @ 4000rpm / 6.4Ps/8000rpm		
EPA Approved	Meet or exceeds EPA clean air requirements and CA Green Sticker		
Spark Plug	Recommended: NGK CR7HSA/NGK or Nipendenso U22FS-U		
Electrode Gap	0.6-0.7mm or 0.023"		
Starting	Electrical starter		
<b>Transmission</b>			
Type	Automatic (C.V.T. V-Belt) with forward/reverse shift		
<b>Chassis</b>			
Overall Length-Width-Height	2125mm / 83.75" - 1010mm / 39.75" - 1170mm / 46.0"		
Wheel Base	1010mm / 39.75"		
Seat Height	710mm / 28.0"		
Dry Weight	170 kg / 375 lbs		
<b>Suspension</b>			
Front	A-arm with dual Adjustable Shocks		
Rear	Swing Arm with Adjustable Shock		
<b>Brakes</b>			
Front	155mm Dual Hydraulic Disc		
Rear	175mm Hydraulic Disc		
<b>Tires</b>			
Front	18/7-10		
Rear	18/8-10		
Tire Pressure	Front	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
	Rear	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
<b>Wheels</b>			
Bolt Pattern	Front	4 x 110mm (P.C.D.)	
	Rear	4 x 110mm (P.C.D.)	
<b>Carburetor</b>			
Make/Size	SVR 22mm with Manual Choke		
Main Jet	0.95mm		
Pilot Jet	0.32mm		
Air Mixture Adjustment	Back out 1½ - 1¾ turns		
Idle Speed	Idle 1700 - 1900rpm		
<b>Sprockets</b>			
Front	520x12t		
Rear	520x32t		
Chain	#520		
<b>Battery</b>			
Jell Acid (Maintenance Free)	12V-5AH - GTX5L		
<b>Fluids</b>			
Fuel	Type	Unleaded Gasoline 92 octane	
	Volume	11 liters / 2.9gal	
Engine Oil	Type	SAE 15W-40	
	Volume	0.9liters / 0.23gal	
Transmission	Type	SAE 80W-90	
	Volume	300cc / 10.2oz	
<b>Safety Features</b>			
Seat Belt	Lap Belt (Standard)		
Remote Stop Switch	Remote Engine Stop Switch (Optional)		
<b>Carrying Capacity</b>			
Maximum Rider Weight	100kg / 200 lbs		
<b>Additional Features</b>			
Rear Cargo Flat Bed (Standard)	Digital dash gauge—Speedometer & Fuel Level (Standard)		
Covered Front Storage Compartment (Standard)	Dash mounted F/R Shift Knob & indicator lights (Standard)		
Trailer Hitch & Accessory Power Outlet (Optional)	Sporty Steering Wheel		
Foot peddle throttle & brakes controls (Standard)	Rear Cargo Basket (Optional)		
Front Cargo Rack (Optional)	Detachable Spot Light (Optional)		
Carpeted floor mat (Optional)			

